
North America's Leader in Hazardous Material Information Management
1905 Aston Avenue, Carlsbad, CA 92008
Phone (800) 451-8346 Fax (760) 602-8888

MSDS PRODUCT INFORMATION

Date: 10/07/2005
To: MSDS Requester
From: 3E Company
Subject: The MSDS you have requested

☐ MSDS NOT REQUIRED

In response to your request for a Material Safety Data Sheet, according to the OSHA Hazard Communication Standard (Right-to-Know), the following item is an article. Articles are defined in 29 CFR 1910.1200(c). Products such as Drugs, cosmetics, food, or alcoholic beverages, wood or wood products, and tobacco or tobacco products, as defined in 29 CFR 1910.1200(b)(6), are exempt from the Hazard Communication Standard. Items that are considered articles, as defined in 29 CFR 1910.1200(c), are also exempt from this Standard. Therefore, the manufacturer is not required to provide an MSDS for this product.

☐ MSDS DISCONTINUED PRODUCT

In response to your request for a Material Safety Data Sheet, the manufacturer has discontinued the product listed below. The MSDS Attached is the most current version, or an MSDS is no longer available.

☒ MSDS BEST COPY AVAILABLE

The MSDS attached is the best copy available from the manufacturer.

☐ MANUFACTURER NO LONGER IN BUSINESS

In response to your request for a Material Safety Data Sheet, a current MSDS could not be obtained for this product. It has been determined that the manufacturer listed below is no longer in business. A current address and phone number could not be located.

Manufacturer: Henry Company
Product Name: Henry 555

MATERIAL SAFETY DATA SHEET
May be used to comply with
OSHA's Hazard Communication
Standard, 29 CFR 1910.1200.
Standard must be consulted
for specific requirements.

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health
Administration
(Non Mandatory Form)
Form Approved
OMB No. 1218-0072

H.M.I.S. RATING
HEALTH: 2
FLAMMABILITY: 2
REACTIVITY: 0
PERSONAL PRO-
TECTIVE EQUIP.:

IDENTITY (as used on label and list)

Henry #555

NOTE: Blank spaces are not permitted, if any item is not applicable, or no
information is available, the space must be marked to indicate that.

SECTION I

Manufacturer's Name HENRY CO., MONSEY DIVISION	Emergency Telephone Number 610-933-8888
ADDRESS (Number, Street, City, State and Zip Code) P.O. BOX 368	Telephone Number for Information 610-933-8888
COLD STREAM ROAD	Date Prepared Supersedes Sheet # 1/18/00 NONE 309
KIMBERTON, PA 19442	Signature of Preparer (optional)

SECTION II HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous Components (Specify Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(optional)
CAS#				
PETROLEUM DISTILLATE	8052-41-3		100 ppm 2mm Hg @68°F	
ALUMINUM METAL	7429-90-5		10 mg/M ³	
ASPHALT	8052-42-4		5 mg/M ³	
PETROLEUM DISTILLATE	64742-95-6		50 ppm (245 mg/M ³) for an 8 hr. workday	

THERE ARE NO SARA INGREDIENTS IN THIS MATERIAL IN EXCESS OF DEMINIMUS AMOUNTS.

SECTION III PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Pt.	310 - 400°F	Weight per gallon	7.48#
Vapor Pressure(mm Hg)	2 @68°F	Melting Point	N/A Liquid
Vapor Density(Air = 1)	Heavier	Evaporation Rate (Butyl Acetate = 1)	Slower
Solubility in Water	None		
Appearance and Odor	Black Fluid, Odor Characteristic of Petroleum Solvent		

SECTION IV FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method Used): SETA 105°F	Flammable Limits	LEL 0.9%	UEL 6.0%
---------------------------------------	------------------	----------	----------

EXTINGUISHING MEDIA: Foam, CO₂, Dry Chemical, Water Fog, Spray

SPECIAL FIRE FIGHTING PROCEDURES: During emergency conditions, overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Do not mix or store with strong oxidants like liquid chlorine or oxygen. Keep containers tightly closed. Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions

SECTION V REACTIVITY DATA

STABILITY	Unstable		Conditions to avoid
	Stable	X	

INCOMPATIBILITY (Materials to Avoid): Strong oxidants, acid

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Fumes, Smoke, and Carbon Dioxide. Carbon Monoxide if combustion is incomplete.

HAZARDOUS POLYMERIZATION	May Occur		Conditions to Avoid
	Will not Occur	X	

SECTION VI HEALTH HAZARD DATA

ROUTE(S) OF ENTRY: Inhalation? YES Eyes? YES Skin? YES Ingestion? YES

HEALTH HAZARDS (Acute and Chronic):

IF INHALED: Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.

IF INGESTED: Swallowing can cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

IF ON SKIN: Prolonged or repeated skin contact can cause moderate irritation or dermatitis.

IF IN EYES: Overexposure to vapors causes eye irritation, blurred vision, dizziness, headaches even unconsciousness.

EMERGENCY AND FIRST AID PROCEDURES:

IF IN EYES: Flush with large amounts of water, lifting upper and lower lids occasionally. Get medical attention.

IF ON SKIN: Remove contaminated clothes, and wash with waterless handcleaner or soap and water.

IF INGESTED: Do not induce vomiting.

IF INHALED: Remove from vapors immediately. If overcome, call a physician. If breathing stopped or irregular, start resuscitation or administer oxygen as needed.

SECTION VII--PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove sources of ignition. Keep people away. Recover free liquid. Add absorbent (sand, earth, sawdust, etc.) to spill area. Avoid breathing vapors. Ventilate confined spaces. Open all windows and doors. Keep products out of sewers and watercourses by diking or impounding and advise authorities.

WASTE DISPOSAL METHOD: Assure conformity with applicable disposal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep containers closed when not in use. Do not handle or store near heat, sparks, flame, or strong oxidants. Adequate ventilation required.

OTHER PRECAUTIONS: Avoid breathing vapors. Avoid prolonged or repeated contact with skin. Remove contaminated clothing and laundry before reuse. Remove contaminated shoes and thoroughly dry before reuse. Wash skin thoroughly with soap and water after contact.

SECTION VIII CONTROL MEASURES

RESPIRATORY PROTECTION (Specify Type): Use hydrocarbon vapor canister or supplied-air respiratory protection in confined or enclosed spaces--if needed.

VENTILATION	LOCAL EXHAUST:	Face Velocity 60 fpm
	SPECIAL:	Use with adequate ventilation
	MECHANICAL (General):	Not applicable
	OTHER:	Not applicable

PROTECTIVE GLOVES: Use chemical-resistant gloves if needed to avoid repeated or prolonged skin contact.

EYE PROTECTION: Use splash goggles or face shield when eye contact may occur.

OTHER PROTECTIVE CLOTHING OR EQUIP: Use chemical-resistant apron or other clothing to avoid repeated or prolonged skin contact.

WORK HYGIENIC PRACTICES: Use good hygiene when using all chemical products.